Dry aging cabinet code: 221433

Body, door frame, and door handle made of 18/8 stainless steel.
Door made of 2 layers of Low-E tinted tempered glass which increases energy efficiency by blocking infrared light and UV from the outside while preventing the heat from transferring inside.
Door lock is included.
Distilled water container made of ABS – distilled water must be filled manually.
Display notification and audible alarm when the water tank's humidity falls below 15%.
Alarm indicating the door open for more than 3.5 minutes – protection against uncontrolled disruption of the conditions in the chamber.
Built-in UVC sterilisation lamp to prevent bacterial growth and guarantee safe environment for the meat; when the door is opened during the seasoning process, bacteria do not have a chance to develop.
Forced cooling using a ventilator which ensures the required level of air circulation.
LED lights placed on both sides of the chamber and on the ceiling.
Max. load per hook: 25 kg.
Max. load of the hanging rod: 50 kg.
Adjustable humidity range: 60-85%.
Current humidity level is displayed on the panel. Max. load per shelf: 30 kg.
In the cabinet there are:
– 3 shelves,
– 1 hanging rod,
– 3 hooks,
– salt tray (salt not included),
all elements above are made of 18/8 stainless steel.





SPECIFICATIONS

Adjustable	Yes	Marketing Packaging Type	Box
Door type	Hinged	Shelf / tray type	Grating
Number of shelves	3	Usable volume (L)	233
Length (mm)	760	Max load	25
Width (mm)	595	Max load unit	kg/shelf
Height (mm)	1270		
Measurements	760x595x(H)1270		
Main materials	Plastics, Metals, Glass		

TRANSPORT SPECIFICATIONS

EAN	8711369221433	Plastic packaging (gram)	1500
Intrastat code	84185090	Country of origin	China
Sales units per pallet	1	GS1 Packed per	1
		Gross weight (kg)	78