

Freezer single door Profi Line 670L

232132

Inner and outer housing are made of high-quality stainless steel, except the outer rear cover which is made of galvanized steel. Self-closing lockable door(s) with comfortable curved door handle(s). Forced air cooling with auto-defrost, compressor placed above the chamber. 60 mm thick polyurethane foam insulation. With adjustable shelving, fits containers up to GN 2/1. Digital display and electronic thermostat. Fitted with 4 wheels of which 2 are castor wheels. Climate class: 5.

Chamber dimensions: 610x700x(H)1540 mm. 3 shelves GN 2/1 (650x530 mm) included. Spread load capacity of 40 kg each. Energy label: C (A+++–G). Coolant: R290. Weight: 120 kg.



Specifications

Voltage	: 230
Temp range from (°C)	: -22°C
Temp range to (°C)	: -17°C
Refrigerant	: R290
Insulation thickness (mm)	: 60
Climate class	: 5 (40°C 40% RH)
Energy label	: C
Materials	: Stainless steel

Packed per	: 1
Length (mm)	: 730
Width (mm)	: 800
Height (mm)	: 2096
Internal length (mm)	: 610
Internal width (mm)	: 635
Internal height (mm)	: 1540
GN size	: GN 2/1
Power (input) (W)	: 600
Measurements	: 730x800x(H)2096

Transport specifications

EAN	: 8711369232132
Intrastat code	: 84184080
Gross weight (kg)	: 130
Net weight (kg)	: 117.64
Plastic packaging (gram)	: 6050

HENDI B.V.

Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.

ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH

Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.

Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA

5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.

Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu