

Dry aging cabinet

204962

Body, door frame, and door handle made of AISI 304 stainless steel. Door made of 2 layers of Low-E tinted tempered glass which increases energy efficiency by blocking infrared light and UV from the outside while preventing the heat from transferring inside. Door lock is included. Distilled water container made of ABS – distilled water must be filled manually. Display notification and audible alarm when the water tank's humidity falls below 15%. Alarm indicating the door open for more than 3.5 minutes – protection against uncontrolled disruption of the conditions in the chamber. Built-in UVC sterilisation lamp to prevent bacterial growth and guarantee safe environment for the meat; when the door is opened during the seasoning process, bacteria do not have a chance to develop. Forced cooling using a ventilator which ensures the required level of air circulation. LED lights placed on both sides of the chamber and on the ceiling. Max. load per hook: 25 kg. Max. load of the hanging rod: 50 kg. Temperature range: 1-25 °C. Adjustable humidity range: 60-85%. Current humidity level is displayed on the panel. Refrigerant: R600a.

Max. load per shelf: 25 kg. In the cabinet there are: – 3 shelves, – 1 hanging rod, – 3 hooks, – salt tray (salt not included), all elements above are made of AISI 304 stainless steel.



HENDI B.V.
 Innovatielaan 6
 6745 XW De Klomp, The Netherlands
 T: +31 (0)317 681 040
 E: info@hendi.eu

HENDI Polska Sp. z o.o.
 ul. Firmowa 12
 62-023 Robakowo, Poland
 T: +48 61 6587000
 E: info@hendi.pl

HENDI GmbH
 Ehrling 15
 5112 Lamprechtshausen, Austria
 T: +43 (0) 6274 200 10 0
 E: office.austria@hendi.eu

HENDI S.R.L.
 Str. 13 decembrie 94A, Hala 14
 Braşov, 500164, Romania
 T: +40 268 320330
 E: office@hendi.ro

PKS HENDI South East Europe SA
 5 Metsovou Str.
 18346 Moschato, Athens, Greece
 T: +30 210 4839700
 E: info@pks-hendi.com

HENDI Italia S.R.L.
 Via Leonardo da Vinci 4
 39100 Bolzano (BZ), Italy
 T: 800 727 438
 E: office.italy@hendi.eu

Specifications

Interior material	: 18/10 Stainless steel
Usage area	: Indoor
Machine type	: Freestanding
Voltage	: 220-240
Temp range from (°C)	: 1°C
Temp range to (°C)	: 25°C
Agregate placement	: Bottom
Refrigerant	: R600a
Cooling system	: Dynamic
Insulation spec	: Cyclopentan
Insulation thickness (mm)	: 50
Climate class	: 8 (24°C 55% RH)
Energy label	: B
Cord length (mm)	: 2000
Reversible door	: Yes
Included accessories	: Lock key
Materials	: ABS (Acrylonitril-butadiene-styrene), Hardened glass, 18/10 Stainless steel
Transparent door	: Yes
Packed per	: 1
Packaging type	: Box
Length (mm)	: 695
Width (mm)	: 760
Height (mm)	: 1720
Usable volume (L)	: 352
Capacity value	: 126
Capacity unit	: kg
Max load	: 30
Tray support spacing (mm)	: 90
Noise level (dB)	: 69
Power (input) (W)	: 170
Control panel	: Digital
Number of doors	: 1
Number of shelves	: 3
Measurements	: 695x760x(H)1720
Shelf type	: Greting
Adjustable	: Yes

Transport specifications

EAN	: 8711369204962
Intrastat code	: 84385000
Gross weight (kg)	: 95
Net weight (kg)	: 81.5
Plastic packaging (gram)	: 2530

HENDI B.V.
Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.
ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH
Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.
Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA
5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.
Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu