

## Condensation hood for ovens code: 219843

Single-phase engine with one rotation direction.

Maximum air flow: from 400 m<sup>3</sup>/h to 600 m<sup>3</sup>/h.

Housing made of highest quality stainless steel 18/8.

Connection to fresh water 3/4" with water pressure 100-200 kPa (1.0-2.0 bar).

No connection to permanent duct or ventilation chimney required.

Included:

– water connection hose with 3/4" thread, 1.5 m long.

– 1 labyrinth filter.

– electric cable 1.6 m long.

– sewer drain Ø 30 mm.



### SPECIFICATIONS

|                          |                        |
|--------------------------|------------------------|
| Adjustable               | No                     |
| Power (input) (W)        | 600                    |
| Marketing Packaging Type | Brown box with sticker |
| Length (mm)              | 860                    |
| Width (mm)               | 730                    |
| Height (mm)              | 308                    |

### TRANSPORT SPECIFICATIONS

|                        |               |
|------------------------|---------------|
| EAN                    | 8711369219843 |
| Intrastat code         | 84148080      |
| Sales units per pallet | 2             |

|                      |    |
|----------------------|----|
| Marketing Packed per | 1  |
| Programmable         | No |
| Weight of item (kg)  | 26 |

|                          |       |
|--------------------------|-------|
| Plastic packaging (gram) | 15    |
| Country of origin        | Italy |
| GS1 Packed per           | 1     |
| Gross weight (kg)        | 27.82 |