

Convection steam oven CONTROL 11x GN1/1

219935

Chamber made of 18/8 stainless steel. Pressed chamber with rounded corners for easy cleaning. Insulated to retain heat – energy-efficient and safe. Fitted with LED lighting for a clear view of the cooking process. Drip tray with integrated drain in the door for effective condensation management. Adjustable feet ensure stable and level placement. Door features: Double-glass door stays cool to the touch – gravity ventilation between layers. Lockable in 4 positions: 60°, 90°, 120°, and 180°. Hinged on the right side. Removable inner glass pane. Door seal made of thick silicone, mounted in the housing. Water protection rating: IPX4. Required connections: electricity, treated water, and drainage system. Operated electromechanically using 3 control knobs. Temperature resistance: 100°C to 270°C. Timer: up to 120 minutes, or continuous operation. 2 cooking modes: - Convection - Convection-steam (combi) Steam is generated by spraying water directly onto the fan. Electronically controlled in 5 steps for precise humidity regulation.

Production capacity: 165-220 dishes/day. Tray support spacing: 68 mm. 2 fans with auto-reverse. Compatible with oven base: 220795.



HENDI B.V.

Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.

ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH

Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.

Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA

5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.

Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu



HENDI

Tools for Chefs

Specifications

| | |
|---------------------------|---|
| Usage area | : Kitchen, Indoor |
| Oven chambers | : 1 |
| Voltage | : 400 |
| Rated Frequency (Hz) | : 50 Hz |
| Temp range from (°C) | : 100°C |
| Temp range to (°C) | : 270°C |
| Unit temperature | : Celsius |
| Timer | : 120 |
| Timer unit | : Minutes |
| Heating element | : Heater |
| Ingress protection | : IPX4 |
| Protections | : Overheat protection, Thermal fuse, Water proof |
| Nestable | : No |
| Reversible door | : No |
| Water connection | : Yes |
| Plumber needed | : Yes |
| Electrician needed | : Yes |
| Transparent door | : Yes |
| Marketing Packed per | : 1 |
| Marketing Packaging Type | : Box |
| Length (mm) | : 730 |
| Width (mm) | : 855 |
| Height (mm) | : 1130 |
| Weight of item (kg) | : 113.8 |
| Internal length (mm) | : 590 |
| Internal width (mm) | : 372 |
| Internal height (mm) | : 855 |
| Sizes that fit | : GN 1/1 |
| Capacity value | : 11 |
| Capacity unit | : Trays |
| Max load | : 4 |
| Tray support spacing (mm) | : 68 |
| Power (input) (W) | : 15400 |
| Control panel | : Analog |
| Programmable | : Yes |
| Probe | : No |
| Number of fans | : 2 |
| Measurements | : 730x855x(H)1130 |
| Main materials | : Metals, Glass |
| Materials | : Double pane glass, 18/0 Stainless steel |
| Interior material | : 18/10 Stainless steel |

Transport specifications

| | |
|--------------------------|-----------------|
| EAN | : 8711369219935 |
| Intrastat code | : 84198180 |
| Gross weight (kg) | : 116 |
| Net weight (kg) | : 98.02 |
| Sales units per pallet | : 1 |
| Plastic packaging (gram) | : 100 |

HENDI B.V.

Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.

ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH

Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.

Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA

5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.

Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu