

Convection steam oven CONTROL 5x GN 1/1

229583

Chamber made of 18/8 stainless steel. Pressed chamber with rounded corners for easy cleaning. Insulated to retain heat – energy-efficient and safe. Fitted with LED lighting for a clear view of the cooking process. Drip tray with integrated drain in the door for effective condensation management. Adjustable feet ensure stable and level placement. Door features: Double-glass door stays cool to the touch – gravity ventilation between layers. Lockable in 4 positions: 60°, 90°, 120°, and 180°. Hinged on the right side. Removable inner glass pane. Door seal made of thick silicone, mounted in the housing. Water protection rating: IPX4. Required connections: electricity, treated water, and drainage system. Operated electromechanically using 3 control knobs. Temperature resistance: 100°C to 270°C. Timer: up to 120 minutes, or continuous operation. 2 cooking modes: - Convection - Convection-steam (combi) Steam is generated by spraying water directly onto the fan. Electronically controlled in 5 steps for precise humidity regulation.

Production capacity: 75-100 dishes/day. Tray support spacing: 68 mm. 1 fan with auto-reverse. Compatible with oven base: 229521.



HENDI B.V.

Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.

ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH

Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.

Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA

5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.

Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu



HENDI

Tools for Chefs

Specifications

Usage area	: Indoor, Kitchen
Oven chambers	: 1
Voltage	: 400
Rated Frequency (Hz)	: 50 Hz, 60 Hz
Temp range from (°C)	: 100°C
Temp range to (°C)	: 270°C
Unit temperature	: Celsius
Timer	: 120
Timer unit	: Minutes
Heating element	: Heater
Ingress protection	: IPX4
Protections	: Overheat protection, Thermal fuse, Water proof
Nestable	: No
Reversible door	: No
Water connection	: Yes
Plumber needed	: Yes
Electrician needed	: Yes
Transparent door	: Yes
Marketing Packaging Type	: Box
Length (mm)	: 730
Width (mm)	: 855
Height (mm)	: 700
Weight of item (kg)	: 78.4
Internal length (mm)	: 590
Internal width (mm)	: 370
Internal height (mm)	: 425
GN size	: GN 1/1
Capacity value	: 5
Capacity unit	: Trays
Max load	: 4
Max load unit	: kg/tray
Tray support spacing (mm)	: 68
Power (input) (W)	: 7800
Control panel	: Analog
Programmable	: No
Probe	: No
Number of doors	: 1
Number of fans	: 1
Measurements	: 730x855x(H)700
Main materials	: Metals, Glass
Materials	: Double pane glass, 18/0 Stainless steel
Interior material	: 18/8 Stainless steel

Transport specifications

EAN	: 8711369229583
Intrastat code	: 84198180
Gross weight (kg)	: 77
Net weight (kg)	: 60.36
Sales units per pallet	: 2
Plastic packaging (gram)	: 40

HENDI B.V.

Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.

ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH

Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.

Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA

5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.

Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu