

Convection steam oven, Touch, electric code: 229620

Made of 18/8 stainless steel.
 Rounded edges for easy cleaning.
 Safety door with opening locks at 60°, 90°, 120°, and 180°.
 Double-glazed door with LED lighting and gravity cooling.
 Right-hinged door.
 Durable silicone gasket – easy to replace without service support.
 IPX5 rating (electric).
 Adjustable feet for stable and level installation.
 Temperature resistance: 30°C–270°C.
 7-inch full-colour TFT touch panel.
 Menu available in 42 languages, including English and Polish.
 USB port and Wi-Fi for recipe transfer and software updates (including HACCP data).

Additional features:

Preheating, holding, cooldown.
 Proofing and holding cabinet chamber.
 Delayed start (up to 24 hours).
 500 built-in recipes, 5 fan speeds, 10 steam levels.
 DELTA T cooking mode.

- + HACCP functionality to download oven parameters for process control.
- + 500 recipe cookbook for quick access to cooking presets and ideas.
- + Safety door with multiple opening angles (60°, 90°, 120°, 180°) to prevent burns.
- + Flow+ patented technology for improved air circulation and even cooking across all levels.

Multilevel Cooking – Prepare different dishes simultaneously under the same conditions; the oven notifies when to remove each tray.
 Multi-point Probe – Measures internal food temperature at three points for precision cooking.
 Automatic Washing System – 4 cleaning programs (ECO, NORMAL, INTENSE, RINSING) with up to 30% water savings.

Patented technologies:

Flow+ – Redesigned fan deflector ensures perfect air circulation and even cooking across all tray levels.
 Humid+ – Efficient humidification system draws water directly from the fan for optimal moisture and reduced water consumption.
 Dry+ – Computer-controlled valve manages chamber humidity for ideal cooking conditions by removing excess moisture. With direct steam and touch screen controls.
 Fits up to 5 x GN 1/1 trays.
 Performance: 70-100 dishes/day.
 Tray support spacing: 68 mm.
 1x auto-reverse fan.



Code	V	LxWxH (W)
229620	400	730x784x(H)700