

Water softener, automatic code: 230459

Using water softeners helps extend the life cycle of catering equipment.

The softeners are based on an ion-exchange process wherein the calcium and magnesium ions that cause water hardness are captured by ion exchange resin inside the softener.

It helps reduce maintenance costs thanks to effective prevention of lime scale deposits. The device is fitted with a control head that makes it possible to configure working parameters of the water softening system as required.

The elements inside the head are made of high quality ceramics, resistant to abrasion, corrosion and build-up of impurities (e.g. iron).

This technology assures perfect seal inside the controller and therefore long and trouble-free operation.

Water connection diameter 3/4".

Working pressure: 1.5-6.0 bar.

Working ambient temperature: 5 – 38°C.

Max. supply water temperature: 38°C.

Regeneration time: 37 min.

Output for 10°dH – 1200 L.

Resin bed 4,0 L.

Regeneration tank: 8 kg.

Maximum water flow: 5 L/min.

Regeneration salt consumption per 1 cycle: 0.5 kg. The automatic resin bed regeneration process using brine is initiated automatically.

Using the control panel the working time, regeneration time and water amount to be treated can be set.

Automatic lock prevents unwanted access.

Weight: 7.7 kg.



Code	V	W	LxWxH (W)
230459	230	18	214x417x(H)505