

Digital bar blender with sound enclosure

230695

Housing made of ABS. Transparent polycarbonate jug with firm PP lid and small polycarbonate cover. Replaceable stainless steel blades with titanium coating. Pulse switch for blending function. Removable, break resistant jug withstands temperatures from -40°C to 90°C . Jug capacity: 2.5 L. Overheating and overcurrent protection. This blender can do it all: fruit, vegetables, cocktails, smoothies, desserts and even crushed ice.

Sound enclosure made of polycarbonate. Safety lock system to prevent accidental activation of the blender if the jug is not in place or the sound enclosure is not fully closed. Digital touch screen control panel. High speed motor with variable speed of the blade from 8350 RPM up to 24800 RPM (without load). 3 speed levels: LOW ca. 8350 RPM, MEDIUM ca. 13500 RPM, HIGH ca. 24800 RPM (without load). 3 timer settings: 30, 45, 90 seconds.



HENDI B.V.

Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.

ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH

Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.

Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA

5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.

Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu



HENDI

Tools for Chefs

Specifications

Usage area	: Kitchen
Not suitable for	: Continuous use
Voltage	: 220-240
Timer	: 90
Timer unit	: Seconds
Cord length (mm)	: 1300
Protections	: Thermal cutout, Electric fuse, Micro switch
Electrician needed	: No
Materials	: ABS (Acrylonitril-butadien-styrene), PC (Polycarbonate), Stainless steel

Packed per	: 1
Packaging type	: Box
Length (mm)	: 250
Width (mm)	: 300
Height (mm)	: 546
Maximum volume (L)	: 2.5
Usable volume (L)	: 2.5
Noise level (dB)	: 85
Power (input) (W)	: 1680
Drive supply	: Electric motor
RPM	: 24800
Control panel	: Digital
Programmable	: No
Number of gears	: 3
Measurements	: 250x300x(H)546
Colour	: Black

Transport specifications

EAN	: 8711369230695
Intrastat code	: 85094000
Gross weight (kg)	: 10.29
Net weight (kg)	: 9.01
Sales units per pallet	: 20
Plastic packaging (gram)	: 326

HENDI B.V.

Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.

ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH

Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.

Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA

5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.

Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu