

Freezing cabinet with white painted steel casing

236062

External housing made of white coated steel. Static cooling. Rear external wall and bottom made of galvanised sheet metal. Interior made of ABS plastic. Thick cyclopentane foam insulation (C5H10) (up to 65 mm), depending on the model, for greater temperature stability inside the cabinet. Highly accurate digital thermostat makes it possible to precisely determine storage temperature. Adjustable shelves with a load capacity of 30 kg each, provided that the weight in the cooling display cabinet is distributed evenly. Fixed shelves with freezing system components, with a load capacity of 25 kg each, provided that the weight in the freezing display cabinet is distributed evenly. Additional shelf at the bottom of the chamber to increase storage space (selected models only – see table). Electromechanical control with electronic display for indicating set and actual temperature. With 2 feet at the front allow for limited height adjustment and 2 castors at the back, ideal for moving the cabinet (only cabinets with the capacity of 400 and 600 l). Self-closing doors to reduce electricity consumption. Locking doors (with a key).

Fixed shelves 2x458x445 mm. Opening door alarm.



HENDI B.V.

Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.

ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH

Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.

Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA

5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.

Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu



HENDI

Tools for Chefs

Specifications

Voltage	: 220-240
Temp range from (°C)	: -20°C
Temp range to (°C)	: -15°C
Unit temperature	: Celsius
Refrigerant	: R600a
Cooling system	: Static
Insulation thickness (mm)	: 70
Climate class	: 3 (25°C 60% RH)
Reversible door	: Yes
Electrician needed	: No
Marketing Packed per	: 1
Length (mm)	: 589
Width (mm)	: 655
Height (mm)	: 838
Internal length (mm)	: 493
Internal width (mm)	: 477
Internal height (mm)	: 647
Maximum volume (L)	: 200
Power (input) (W)	: 111
Measurements	: 589x655x(H)838
Colour	: White

Transport specifications

EAN	: 8711369236062
Intrastat code	: 84185011
Gross weight (kg)	: 36.76
Net weight (kg)	: 32.57
Sales units per pallet	: 2
Plastic packaging (gram)	: 122

HENDI B.V.

Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.

ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH

Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.

Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA

5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.

Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu