

Dishwasher 50x50, electronic control code: 238752

Double-skin housing and door made of stainless steel 18/8 for thermal and acoustic insulation.

Digital control panel with 4 washing cycles: 60 / 120 / 180 / 480 s.

Peristaltic rinse aid and detergent dispensers.

Built-in drain pump for installations without gravity drainage.

Double filtration system for cleaner wash water.

Thermostop system ensures rinsing starts at 85°C.

Capacity: up to 60 / 30 / 20 / 8 baskets per hour.

Water consumption per cycle: 2.4–2.6 L.

Washing temperature: 50–60°C.

Rinse temperature: 85°C.

Safety thermostat for boiler up to 110°C.

IPX1 protection class. Basket holder rails with rounded corners.

Angled control panel for comfortable and ergonomic use.

Suitable for washing mugs, cups, glasses, cutlery, and plates.

Suitable for items up to 320 mm high.

Stainless steel wash arms and polymer rinse arms.

Rinse water temperature: from 82°C to 85°C.

Boiler capacity/power: 6 L / 4 kW.

Tank capacity/power: 23 L / 2.5 kW.

Wash pump power: 0.4 kW.

Exclusive wash pumps mounted directly at the bottom of the tank.

Vertically adjustable legs: approx. 10 mm, Ø40 mm.

Convertible to 230 V installation (technician required).

Accessories included:

- 2x universal baskets 500x500x(H)105 mm.
- 1x cutlery basket 110x110x(H)130 mm.
- Water supply hose, 1.5 m, with ¾" inner thread.
- Drain hose, 2 m, Ø25 mm.
- Power cord without plug.

-  Double-skin construction for enhanced heat retention and noise reduction.
-  Built-in drain pump supports flexible installation without gravity drainage.
-  Integrated detergent and rinse aid dispensers support consistent washing results.
-  4 washing cycles support different washing loads and service needs.





238752

400

4900

582x610x(H)822