

Induction cooker model 1800

239209

ABS housing. Digital power, temperature and timer setting. Settings immediately respond to high-low. Maximum load of the induction cooker: 15 kg. Suitable for pans with bottom diameter between 120 and 260 mm.



Specifications

Usage area	: Kitchen
Voltage	: 230
Temp range from [°C]	: 60°C
Temp range to [°C]	: 240°C
Unit temperature	: Celsius
Heating element	: Induction
Electrician needed	: No
Materials	: ABS (Acrylonitril-butadien-styrene)
Packed per	: 1
Packaging type	: Box
Length (mm)	: 319
Width (mm)	: 355
Height (mm)	: 67
Power (input) (W)	: 1800
Programmable	: No
Measurements	: 319x355x(H)67

Transport specifications

EAN	: 8711369239209
Intrastat code	: 84198180
Gross weight (kg)	: 3.02
Net weight (kg)	: 2.5
Export carton length (mm)	: 370
Export carton width (mm)	: 370
Export carton height (mm)	: 448
Quantity per export carton	: 4
Sales units per pallet	: 96
Plastic packaging (gram)	: 80

HENDI B.V.
 Innovatielaan 6
 6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.
 ul. Firmowa 12
 62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH
 Ehrling 15
 5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.
 Str. 13 decembrie 94A, Hala 14
 Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA
 5 Metsovou Str.
 18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.
 Via Leonardo da Vinci 4
 39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu