

Tray sealer Supreme

976722

Seal the most popular tray types on the market with optional dies. Robust and stable stainless steel construction. Equipped with a lid with spring mechanism for easy and safe opening. Welding process is almost effortless; resistance is minimal due to bearings and special sliding material. Pressure absorber ensures a tight seal and prevents packages from crushing. Insulated handle made of damage-resistant plastic. Automatic guillotine with safety knife in specially designed cover; cutting takes place just behind the sealed container in a special strip (air-cut technology). Film feeder with a stretcher prevents the film from curling up. Sealing surface has titanium coating that prevents film sticking and enables a fast seal in 1-3 seconds (depending on film thickness). High power heaters reduce heat-up time. Warm-up time after start-up to full operational mode – approximately 8-10 minutes. Knob with fine adjustment of sealing temperature from 50-210°C. Color-coded LEDs for monitoring appliance performance. Overheat lock, overheat protection, illuminated safety switch. Anti-slip feet ensure stability of the unit during operation and protect the tabletop from scratches. Sealing of trays up to tray size 235x190x(H)155 mm and cups up to (H)170 mm. Maximum film roll size: width 187 mm, ø170 mm – film sold separately (970720). Equipped with aluminium die for 227x178 mm containers (805572), without divider. Detachable power cord, 1.5 m, grounded. Power: 700 W Power supply: 230 V Net weight: 10 kg.



Specifications

Usage area	: Indoor
Voltage	: 230
Temp range from [°C]	: 50°C
Temp range to [°C]	: 210°C
Unit temperature	: Celsius
Heating element	: Heater
Cord length (mm)	: 1500
Protections	: Thermal cutout, Overheat protection
Electrician needed	: No
Packed per	: 1
Length (mm)	: 247
Width (mm)	: 637
Height (mm)	: 258
Weight of item (kg)	: 10
Power (input) (W)	: 700
Control panel	: Analog
Programmable	: No
Measurements	: 247x637x(H)258

Transport specifications

EAN	: 8711369976722
Intrastat code	: 84224000
Gross weight (kg)	: 12.35
Net weight (kg)	: 10.21
Sales units per pallet	: 15

HENDI B.V.
 Innovatielaan 6
 6745 XW De Klomp, The Netherlands
 T: +31 (0)317 681 040
 E: info@hendi.eu

HENDI Polska Sp. z o.o.
 ul. Firmowa 12
 62-023 Robakowo, Poland
 T: +48 61 6587000
 E: info@hendi.pl

HENDI GmbH
 Ehrling 15
 5112 Lamprechtshausen, Austria
 T: +43 (0) 6274 200 10 0
 E: office.austria@hendi.eu

HENDI S.R.L.
 Str. 13 decembrie 94A, Hala 14
 Braşov, 500164, Romania
 T: +40 268 320330
 E: office@hendi.ro

PKS HENDI South East Europe SA
 5 Metsovou Str.
 18346 Moschato, Athens, Greece
 T: +30 210 4839700
 E: info@pks-hendi.com

HENDI Italia S.R.L.
 Via Leonardo da Vinci 4
 39100 Bolzano (BZ), Italy
 T: 800 727 438
 E: office.italy@hendi.eu